



100-110 mm STROKLU ÇİFT SİLİNDİRLİ KRANK MİLİ  
( MODEL : 7716-A, 7720, 7726, 7728, 7732 - 9219-A, 9224, 9234, 9239 - 11025 )

**MONTAJ TALİMATI**  
Blok Montajında Standart Olarak  
2 adet Arka Kapak Contası Kullan  
Krank Eksenal Yatak Boşluğu:  
Minimum : 0.20 mm  
Maksimum : 0.35 mm.  
Olacak Şekilde Ayarla

ÖLÇÜ	ANA MUYLU Çap "D1" mm.	ANA MUYLU Çap "D2" mm.	KOL MUYLUSU Çap "d" mm.
STD.	$\frac{70.00}{69.99}$	$\frac{63.45}{63.44}$	$\frac{63.48}{63.47}$
.010 us	$\frac{69.75}{69.74}$	$\frac{63.19}{63.18}$	$\frac{63.22}{63.21}$
.020 us	$\frac{69.49}{69.48}$	$\frac{62.94}{62.93}$	$\frac{62.97}{62.96}$
.030 us	$\frac{69.24}{69.23}$	$\frac{62.69}{62.68}$	$\frac{62.72}{62.71}$
.040 us	$\frac{68.99}{68.98}$	$\frac{62.44}{62.43}$	$\frac{62.47}{62.46}$
YATAK BOŞLUĞU	0.08 - 0.13	0.08 - 0.11	0.05 - 0.08